

# EdgePro Low Profile® Paver Restraint



## Product Configurations

- Item 1206 EdgePro Low Profile® – 7.5' Boxed
- Item 1306 EdgePro Low Profile® – 7.5' Bundled
- Item 1326 EdgePro Low Profile® – 15' Bundled

## Product Specifications

- Material:** Engineered Rigid PVC Alloy
- Vertical Wall Height:** 1.20 in. (nominal)
- Horizontal Base Width:** 3.00 in. (nominal)
- Vertical Wall Thickness:** 0.23 in. (nominal)
- Horizontal Base Thickness:** 0.25 in. (nominal)
- Weight:** 0.40 lbs. per linear foot (nominal)



## Packaging Specifications

- 12 – 7.5' lengths/box or bundle, 49 boxes or bundles/pallet (4,410 ft.)
- 6 – 15' lengths/bundle, 50 bundles/pallet (4,500 ft.)

## Physical Property Testing

Impact Strength	ASTM Test D-256	Min. 120 in. lbs./in.
Tensile Strength	ASTM Test D-638	Min. 5,000 PSI
Flexural Modules	ASTM Test D-790	Min. 280,000 PSI

EdgePro® Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

## Paver Restraint Accessories

Steel Stakes  
60-Count



Item 1900

8" Spiral  
Steel Spikes  
50# Case



SPIKE8BS

10" Spiral  
Steel Spikes  
50# Case




SPIKE10BS

10" Round  
Steel Spikes  
50# Case



SPIKE10BR

12" Round  
Steel Spikes  
50# Case



SPIKE12BR

10" Spiral  
Nylon Spikes  
200-Count



SPIKE10NS

10" Round  
Nylon Spikes  
200-Count



SPIKE10NR



## Dimex Limited Lifetime Warranty

EdgePro® Paver Restraint products are guaranteed to be free from manufacturing defects and will not to crack, rot, or deteriorate when handled and installed according to recommended guidelines.

# Dimex LLC

28305 State Route 7  
Marietta, OH 45750  
www.edgepro.com

Phone: 740-374-3100  
Toll Free: 800-334-3776  
Fax: 740-374-5420

# EdgePro Low Profile® Rigid Paver Restraint



## Product Configurations

- Item 1207 EdgePro Low Profile® Rigid – 7.5' Boxed
- Item 1307 EdgePro Low Profile® Rigid – 7.5' Bundled
- Item 1327 EdgePro Low Profile® Rigid – 15' Bundled

## Product Specifications

- Material:** Engineered Rigid PVC Alloy
- Vertical Wall Height:** 1.20 in. (nominal)
- Horizontal Base Width:** 3.00 in. (nominal)
- Vertical Wall Thickness:** 0.23 in. (nominal)
- Horizontal Base Thickness:** 0.25 in. (nominal)
- Weight:** 0.50 lbs. per linear foot (nominal)



Intended for 40-60mm paver thicknesses

## Packaging Specifications

- 12 – 7.5' lengths/box or bundle, 49 boxes or bundles/pallet (4,410 ft.)
- 6 – 15' lengths/bundle, 50 bundles/pallet (4,500 ft.)

## Physical Property Testing

Impact Strength	ASTM Test D-256	Min. 120 in. lbs./in.
Tensile Strength	ASTM Test D-638	Min. 5,000 PSI
Flexural Modules	ASTM Test D-790	Min. 280,000 PSI

EdgePro® Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

## Paver Restraint Accessories

Steel Stakes  
60-Count



Item 1900

8" Spiral  
Steel Spikes  
50# Case



SPIKE8BS

10" Spiral  
Steel Spikes  
50# Case




SPIKE10BS

10" Round  
Steel Spikes  
50# Case




SPIKE10BR

12" Round  
Steel Spikes  
50# Case



SPIKE12BR

10" Spiral  
Nylon Spikes  
200-Count



SPIKE10NS

10" Round  
Nylon Spikes  
200-Count



SPIKE10NR

## Dimex Limited Lifetime Warranty

EdgePro® Paver Restraint products are guaranteed to be free from manufacturing defects and will not to crack, rot, or deteriorate when handled and installed according to recommended guidelines.



# Dimex LLC

28305 State Route 7  
Marietta, OH 45750  
www.edgepro.com

Phone: 740-374-3100  
Toll Free: 800-334-3776  
Fax: 740-374-5420