

EdgePro® Paver Restraint



Product Configurations

- Item 1202 EdgePro® Paver Restraint – 7.5' Boxed
- Item 1302 EdgePro® Paver Restraint – 7.5' Bundled
- Item 1322 EdgePro® Paver Restraint – 15' Bundled

Product Specifications

- Material:** Engineered Rigid PVC Alloy
- Vertical Wall Height:** 1.75 in. (nominal)
- Horizontal Base Width:** 3.10 in. (nominal)
- Vertical Wall Thickness:** 0.14 in. (nominal)
- Horizontal Base Thickness:** 0.22 in. (nominal)
- Weight:** 0.42 lbs. per linear foot (nominal)



Packaging Specifications

- 12 – 7.5' lengths/box or bundle, 42 boxes/pallet (3,780 ft.), 48 bundles/pallet (4,320 ft.)
- 6 – 15' lengths/bundle, 50 bundles/pallet (4,500 ft.)

Physical Property Testing

| | | |
|------------------|-----------------|-----------------------|
| Impact Strength | ASTM Test D-256 | Min. 120 in. lbs./in. |
| Tensile Strength | ASTM Test D-638 | Min. 5,000 PSI |
| Flexural Modules | ASTM Test D-790 | Min. 280,000 PSI |

EdgePro® Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

Paver Restraint Accessories

Steel Stakes
60-Count



Item 1900

8" Spiral Steel Spikes
50# Case



SPIKE8BS

10" Spiral Steel Spikes
50# Case




SPIKE10BS

10" Round Steel Spikes
50# Case



SPIKE10BR

12" Round Steel Spikes
50# Case



SPIKE12BR

10" Spiral Nylon Spikes
200-Count



SPIKE10NS

10" Round Nylon Spikes
200-Count



SPIKE10NR



Dimex Limited Lifetime Warranty

EdgePro® Paver Restraint products are guaranteed to be free from manufacturing defects and will not to crack, rot, or deteriorate when handled and installed according to recommended guidelines.

Dimex LLC

28305 State Route 7
Marietta, OH 45750
www.edgepro.com

Phone: 740-374-3100
Toll Free: 800-334-3776
Fax: 740-374-5420

EdgePro® Rigid Paver Restraint



Product Configurations

- Item 1203 EdgePro® Rigid – 7.5' Boxed
- Item 1303 EdgePro® Rigid – 7.5' Bundled
- Item 1323 EdgePro® Rigid – 15' Bundled

Product Specifications

- Material:** Engineered Rigid PVC Alloy
- Vertical Wall Height:** 1.75 in. (nominal)
- Horizontal Base Width:** 3.50 in. (nominal)
- Vertical Wall Thickness:** 0.14 in. (nominal)
- Horizontal Base Thickness:** 0.14 in. (nominal)
- Weight:** 0.50 lbs. per linear foot (nominal)



Packaging Specifications

- 12 – 7.5' lengths/box or bundle, 42 boxes/pallet (3,780 ft.), 48 bundles/pallet (4,320 ft.)
- 6 – 15' lengths/bundle, 50 bundles/pallet (4,500 ft.)

Physical Property Testing

| | | |
|------------------|-----------------|-----------------------|
| Impact Strength | ASTM Test D-256 | Min. 120 in. lbs./in. |
| Tensile Strength | ASTM Test D-638 | Min. 5,000 PSI |
| Flexural Modules | ASTM Test D-790 | Min. 280,000 PSI |

EdgePro® Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

Paver Restraint Accessories

Steel Stakes
60-Count



Item 1900

8" Spiral
Steel Spikes
50# Case



SPIKE8BS

10" Spiral
Steel Spikes
50# Case




SPIKE10BS

10" Round
Steel Spikes
50# Case



SPIKE10BR

12" Round
Steel Spikes
50# Case



SPIKE12BR

10" Spiral
Nylon Spikes
200-Count



SPIKE10NS

10" Round
Nylon Spikes
200-Count



SPIKE10NR



Dimex Limited Lifetime Warranty

EdgePro® Paver Restraint products are guaranteed to be free from manufacturing defects and will not to crack, rot, or deteriorate when handled and installed according to recommended guidelines.

Dimex LLC

28305 State Route 7
Marietta, OH 45750
www.edgepro.com

Phone: 740-374-3100
Toll Free: 800-334-3776
Fax: 740-374-5420