

NovaEdge™ Paver Restraint



Product Configurations

Item 1204 NovaEdge™ Paver Restraint – 7.5' Boxed

Item 1314 NovaEdge™ Paver Restraint – 15' Boxed

Product Specifications

Material: Engineered Rigid PVC Alloy

Vertical Wall Height: 1.75 in. (nominal)

Horizontal Base Width: 2.70 in. (nominal)

Vertical Wall Thickness: 0.16 in. (nominal)

Horizontal Base Thickness: 0.16 in. (nominal)

Weight: 0.32 lbs. per linear foot (nominal)



Packaging Specifications

12 – 7.5' lengths/box, 48 boxes/pallet (4,320 ft.), 6 – 15' lengths/box, 50 boxes/pallet (4,500 ft.)

Physical Property Testing

Impact Strength
Tensile Strength
Flexural Modules

ASTM Test D-256
ASTM Test D-638
ASTM Test D-790

Min. 120 in. lbs./in.
Min. 5,000 PSI
Min. 280,000 PSI

NovaEdge™ Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

Paver Restraint Accessories

Steel Stakes
60-Count



Item 1900

8" Spiral
Steel Spikes
50# Case



SPIKE8BS

10" Spiral
Steel Spikes
50# Case




SPIKE10BS

10" Round
Steel Spikes
50# Case



SPIKE10BR

12" Round
Steel Spikes
50# Case



SPIKE12BR

10" Spiral
Nylon Spikes
200-Count



SPIKE10NS

10" Round
Nylon Spikes
200-Count



SPIKE10NR



Dimex Limited Lifetime Warranty

NovaEdge™ Paver Restraint products are guaranteed to be free from manufacturing defects and will not to crack, rot, or deteriorate when handled and installed according to recommended guidelines.

Dimex LLC

28305 State Route 7
Marietta, OH 45750
www.edgepro.com

Phone: 740-374-3100
Toll Free: 800-334-3776
Fax: 740-374-5420

NovaEdge™ Rigid Paver Restraint



Product Configurations

Item 1205 NovaEdge™ Rigid – 7.5' Boxed

Item 1315 NovaEdge™ Rigid – 15' Boxed

Product Specifications

Material: Engineered Rigid PVC Alloy
Vertical Wall Height: 1.75 in. (nominal)
Horizontal Base Width: 2.70 in. (nominal)
Vertical Wall Thickness: 0.16 in. (nominal)
Horizontal Base Thickness: 0.16 in. (nominal)
Weight: 0.40 lbs. per linear foot (nominal)



Packaging Specifications

12 – 7.5' lengths/box, 48 boxes/pallet (4,320 ft.), 6 – 15' lengths/box, 50 boxes/pallet (4,500 ft.)

Physical Property Testing

Impact Strength	ASTM Test D-256	Min. 120 in. lbs./in.
Tensile Strength	ASTM Test D-638	Min. 5,000 PSI
Flexural Modules	ASTM Test D-790	Min. 280,000 PSI

NovaEdge™ Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

Paver Restraint Accessories

Steel Stakes
60-Count



Item 1900

8" Spiral
Steel Spikes
50# Case



SPIKE8BS

10" Spiral
Steel Spikes
50# Case




SPIKE10BS

10" Round
Steel Spikes
50# Case



SPIKE10BR

12" Round
Steel Spikes
50# Case



SPIKE12BR

10" Spiral
Nylon Spikes
200-Count



SPIKE10NS

10" Round
Nylon Spikes
200-Count



SPIKE10NR

Dimex Limited Lifetime Warranty

NovaEdge™ Paver Restraint products are guaranteed to be free from manufacturing defects and will not to crack, rot, or deteriorate when handled and installed according to recommended guidelines.



Dimex LLC

28305 State Route 7
Marietta, OH 45750
www.edgepro.com

Phone: 740-374-3100
Toll Free: 800-334-3776
Fax: 740-374-5420