

# NovaFlex™ Paver Restraint



## Product Configurations

Item 1216 NovaFlex™ Paver Restraint – 7.5' Boxed

Item 1318 NovaFlex™ Paver Restraint – 15' Boxed

## Product Specifications

**Material:** Engineered Rigid PVC Alloy

**Vertical Wall Height:** 1.75 in. (nominal)  
**Horizontal Base Width:** 2.70 in. (nominal)

**Vertical Wall Thickness:** 0.16 in. (nominal)  
**Horizontal Base Thickness:** 0.16 in. (nominal)

**Weight:** 0.32 lbs. per linear foot (nominal)



## Packaging Specifications

12 – 7.5' lengths/box, 48 boxes/pallet (4,320 ft.), 6 – 15' lengths/box, 50 boxes/pallet (4,500 ft.)

## Physical Property Testing

Impact Strength	ASTM Test D-256	Min. 120 in. lbs./in.
Tensile Strength	ASTM Test D-638	Min. 5,000 PSI
Flexural Modules	ASTM Test D-790	Min. 280,000 PSI

NovaEdge™ Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

## Paver Restraint Accessories

Steel Stakes  
60-Count



Item 1900

8" Spiral  
Steel Spikes  
50# Case



SPIKE8BS

10" Spiral  
Steel Spikes  
50# Case




SPIKE10BS

10" Round  
Steel Spikes  
50# Case



SPIKE10BR

12" Round  
Steel Spikes  
50# Case



SPIKE12BR

10" Spiral  
Nylon Spikes  
200-Count



SPIKE10NS

10" Round  
Nylon Spikes  
200-Count



SPIKE10NR



## Dimex Limited Lifetime Warranty

NovaEdge™ Paver Restraint products are guaranteed to be free from manufacturing defects and will not to crack, rot, or deteriorate when handled and installed according to recommended guidelines.

# Dimex LLC

28305 State Route 7  
Marietta, OH 45750  
www.edgepro.com

Phone: 740-374-3100  
Toll Free: 800-334-3776  
Fax: 740-374-5420